



# NTN BEARING MFG.CORP



## SEALMASTER USTA5000AE-215 Take Up Unit Bearings

Bearing No. USTA5000AE-215

USTA5000AE-215 Bearing 2D drawings and 3D CAD models

|                          |   |
|--------------------------|---|
| Category                 | Take Up Unit Bearings   |
| Inventory                | 0.0   |
| Manufacturer Name        | REGAL BELOIT  |
| Minimum Buy Quantity     | N/A   |
| Weight                   | 12.51   |
| EAN                      | 0662461382356   |
| Product Group            | M06288  |
| Component Description    | Take Up Bearing Only  |
| Rolling Element          | Spherical Roller Bearing  |
| Housing Style            | Unit Only - Half Round Top Angle  |
| Mounting Method          | Adapter Sleeve  |
| Compatible Take Up Frame | Not Specified   |
| Adjustment Travel Length | 0   |
| Insert Part Number       | USI5000A-215  |
| Housing Material         | Cast Iron   |
| Other Features           | Double Row   Solid Housing   Expansion   Felt Labyrinth Seal  |
| Inch - Metric            | Inch  |
| Long Description         | Take Up Bearing Only; 2-15/16" Bore; 1-1/8" Slot Width; 5-53/64" Slot to Slot Distance; Spherical Roller Bearing; Unit Only - Half Round Top Angle; Adapter Sleeve Mount; USI5000A-215 In |
|                          |   |



## NTN BEARING MFG.CORP

|                              |   |
|------------------------------|---|
| Category                     | Take Up Units   |
| UNSPSC                       | 31171533  |
| Harmonized Tariff Code       | 8483.20.40.80   |
| Noun                         | Bearing   |
| Keyword String               | Take Up   |
| Manufacturer URL             | <a href="http://www.emerson-ept.com">http://www.emerson-ept.com</a> |
| Manufacturer Item Number     | USTA5000AE-215  |
| Manufacturer Internal Number | 738069  |
| Weight / LBS                 | 27.555  |
| d                            | 2.938 Inch   74.625 Millimeter                                      |
| Slot Width                   | 1.125 Inch   28.575 Millimeter                                      |
| Slot to Slot Distance        | 5.828 Inch   148.031 Millimeter                                     |