



NTN BEARING MFG.CORP

TIMKEN E-4BF-TRB-2 7/16 Flange Block Bearings



Bearing No. E-4BF-TRB-2 7/16

E-4BF-TRB-2 7/16 Bearing 2D drawings and 3D CAD models

Category	Flange Block Bearings
Inventory	2.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	9.861
EAN	0053893549637
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch - Metric	Inch
Long Description	4 Bolt Square Flange Block; 2-7/16" Bore; 7.6" Bolt Circle; 5-3/8" Bolt Spacing; 1 Piece Solid; Concentric Collar Mount; Cast Iron; Tapered Roller Bearing; 4" Length Thru Bore; Rel
Other Features	Double Row Wide Inner Race With Set Screw



NTN BEARING MFG.CORP

Category	Flange Block
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer URL	http://www.timken.com
Manufacturer Item Number	E-4BF-TRB-2 7/16
Weight / LBS	20
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
d	2.438 Inch 61.925 Millimeter
Nominal Bolt Circle Diameter Round	7.6 Inch 193 Millimeter
Bolt Spacing	5.375 Inch 136.525 Millimeter
D	4 Inch 101.6 Millimeter
Shaft Size	2.4375 in
Shaft Size Type	Imperial
Weight	20 lb
UPC Code	053893549637
Dimension B	4 in
Dimension L	6-7/8 in
Dimension A	3-9/16 in
Dimension J	5-3/8 in
Dimension A ₂	3/16 in
Bolt Diameter	5/8 in
Dimension A ₁	1-1/2 in
Dimension D ¹	5-5/16 in
Dimension d ₁	4-1/16 in
e	0.40
X (if F _a /F _r ≤ e)	0.87
Y (if F _a /F _r > e)	2.17



NTN BEARING MFG.CORP

X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.63
K Factor	1.51
C_{90} Dynamic Load Rating ²	11600 lb
C_0 Static Load Rating	54000 lb
F_{a-max} Maximum Permissible Thrust Load ³	3454 lb
F_{r-max} Maximum Allowable Slip Fit Radial Load ⁴	9500 lb
Max. Speed ⁵	2420 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to conditions of slip fit with set screw mounting or in applications where a large moment loading occur